

Uncontrolled document as of November 24, 2009. Refer to website for up to date specifications.

CASES 1150 Case



1150 Case

- **Watertight, crushproof, and dust proof**
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- Lifetime Guarantee of Excellence

1150 Case Configurations

Cat. #	Description
1150	1150 Case
1150NF	1150 Case (No foam)



Black



Silver



Orange



Yellow



Blue



OD Green*



Desert Tan

*OD Green available upon request

1150 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
9.12" x 7.56" x 4.37" (23.2 x 19.2 x 11.1 cm)		8.18" x 5.68" x 3.62" (20.8 x 14.4 x 9.2 cm)	
Lid Depth	Bottom Depth	Total Depth	
0.75" (1.9 cm)	2.87" (7.3 cm)	3.62" (9.2 cm)	
Weight with foam	Weight without foam	Buoyancy Max.	
1.98 lbs. (0.9 kg)	1.76 lbs. (0.8 kg)	8 lbs. (3.63 kg)	

Range Temperature

-40 / 210° F
(-40 / 99° C)

1150 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- Def Stan 81-41/STANAG 4280

1150 Case Accessories

Cat. #	Description	Sug. Retail
1150PF	Special Application Panel Frame	US\$19.95
1151	3 pc. Replacement Foam Set	US\$14.25
1153	Replacement O-ring	US\$3.40

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com